STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

SEAC-2015/CR-368/TC-1 Environment department, Room No. 217, 2nd floor, Mantralaya Annexe, Mumbai, 400 032. Date: 21 September, 2016.

To, M/s. Sai Jivdani Enterprises. Shop No.1, Jay Apt, Mahesh Park, Tulinj Road, Nallasopara (E), Tal. Vasai, Dist- Thane – 401 209.

Subject: Environment clearance for proposed residential project "Sai Jivdani" at S.No. 177, H.No.1, Nallasopara, Thane by M/s. Sai Jivdani Enterprises.

Sir,

This has reference to your communication on the above mentioned subject. The proposal was considered as per the EIA Notification - 2006, by the State Level Expert Appraisal Committee-II, Maharashtra in its 37th meeting and recommend the project for prior environmental clearance to SEIAA. Information submitted by you has been considered by State Level Environment Impact Assessment Authority in its 91st & 102nd meetings.

2. It is noted that the proposal is considered by SEAC-II under screening category 8(a) B2 as per EIA Notification 2006.

Brief Information of the project submitted by you is as-

1	Name of the Project	"Sai Jivdani" - Residential Commercial Project
2	Project	Mr.Prabhakar Naik
}	Proponent	Sai Jivdani Enterprises
3	Consultant	Name- Mr. H.K. Desai
		Enviro Analysts & Engineers Pvt. Ltd
4	Accreditation of the consultant (NABET Accreditation)	QCI NABET LIST for the Construction Project/ Area Development Project/Township - Accreditation from NABET (Sr. No. 47 as per Rev.33/August 05,2015)
5	Type of Project: Housing Project/Industrial Estate/SRA Scheme/MHAD A/ Township or others	Residential Commercial Project

6	Location of the project	S. No. 17	7, H. No. 1,	Village Nil	S. No. 177, H. No. 1, Village Nilemore, Vasai					
7	Whether in	Vasai Vir	Vasai Virar City Municipal Council (VVCMC)							
	Corporation/Mun icipal/other area									
8	Applicability of the DCR		Vasai Virar		<u> </u>					
9	Note on the initiated work (if applicable)	Total constructed work (FSI+ Non FSI): (5498.24 +3839.11) = 9337.35 sq.m. Date and area details in the necessary approvals issued by the Competent Authority (attach scan copies):- CC is obtained dated 3-9-2002. Revised CC dated 13-06-2011& 31-10-2011								
10	LOI/NOC from MHADA/ other approvals (If Applicable)	Not Appli								
11	Total plot area (sq.m.) Deductions Net Plot Area	Sr. no. 1 2	1 Total Plot area		Details (In sq.m.) 26840.00 5031.766					
12	Permissible FSI (including TDR etc.)	46342.49	Balance Pl sq.m.	ot area	21808.23	4	,			
13	Proposed Built Up Area (FSI & Non FSI)	Non FSI A	=21292.95 S Area= 19117 t Up Area=	7,63 Sq. m. 40409.58 S						
		Existing (in sq.m.) Proposed (in sq.m.) FSI area 16075.61 21292.95 Non FSI Area 3474.68 19117.63 Construction area 19550.34 40409.58				3				
14	Ground Coverage Percentage (%) (Note: percentage of plot not open to sky)	3406.34	Sq. m (18.37	% for Bld	g. 5 & 6)					
15	Estimated cost of the project	Rs.52.94 (Crores							

16	Number of	Bldg No	Configuration	-	Existing/
	Buildings &				Proposed
	configuration(s)	Bldg -1	(G+4)		
		Bldg -2	(G+4)		
		Bldg - 3	(G+4)		
		Bldg-4	(G+4)		
		Bldg -1	(G+4)		
		Bldg -2	(G+4)		EXICTRIC
		Bldg - 3	(G+4)		EXISTING
		Bldg-4	(G+3)		
		Bldg -5	(G+4)		
		Bldg -6	(G+4).		
		Bldg -7	(G+3)		
		Bldg-8	(G+3)		
		Bldg- 5	(Basement+ Stilt+		PROPOSED
		(Wing,	Podium+22)		FOR EC
		A,B,C,D		ſ	(NOT
					CONSTRCTE
		711.6	(O : 5)		D)
!		Bldg 6	(G+7)		CONSTRUC
					TED
				ļ	
17	Number of	Particulars			Details
	tenants and shops		ents (Proposed Bldg 5	& 6)	822
	-		(Proposed Bldg. 5)		34
18	Number of	TYPE		NO. OF	LISERS
	expected	Residential		4110	OSEIGS
	residents/users	Commercial	•	102	
		Total	-	4212	
19	Tenant density per hector	316 Nos. Per He	ectare (For Bldg. 5 &	6)	
20	Height of the	Bldg No	Configuration	ı H	eight in m
	building(s)				
		Bldg -1	(G+4)	14	1.85
	ĺ	Bldg -2	(G+4)]	
		Bldg - 3	(G+4)		İ
'	İ	Bldg- 4	(G+4)		
- 1		7511 -	1,27.	· 1	
		Bldg -1	(G+4)	14	1.85
		Bldg -2	(G+4)		
		Bldg - 3	(G+4)		20
		Bldg- 4	(G+3)		20
1		Bldg -5 Bldg -6	(G+4) (G+4)		·.85
					.85
İ		Bldg -7	(G+3)		.00
-		Bldg-8	(G+3)	12	.20
		Plda 5 (WE)	10 A (Danis	14 70	
		Bldg 5 (Win	g-A, (Basement + S	tilt [70	.00

•

			B,C,D)		+ Podium + 2	22)	
			Bldg 6		(G+7)	- /	23.80
		 	<u>i</u>				<u> </u>
21	Right of way (Width of the road from the nearest fire station to the proposed building(s)	1	0 m wide DP Ro				
22	Turning radius for easy access of fire tender movement from all around the building excluding the width for the plantation		5-9 m				
23	Existing structure(s)	Ex	isting Buildings isting Buildings oposed Building	s Bldg	g. 1-8 (BP-25	82) of	
24	Details of the demolition with disposal (If applicable)	No	t Applicable				
25	Total Water Requirement	Free Tot Sw Fire Sw Fire Sw Fire	y Season esh Water (KLD cycled Water (KLD cycled Water Requi imming Pool M e Fighting (Cum I Tank: 25 cum est Season esh Water(KLD) cycled Water (I tal Water Requi imming Pool M e Fighting (Cum I Tank: 25 cum	KLD): ireme Make t n): U0 for bl ireme MKLD) ireme Make t n): U0	204 nt (KLD): 576 up (Cum): Nil G Tank:100 C dg. 5 & 6 +83 & Source : 188 nt (KLD): 560 up (Cum)-Nil G Tank:100 c	6 Cum for e: VV(Bldg. 6 CMC + Rain water
26	Rain Water Harvesting (RWH)	Level of the Ground Water Table: Up to 3.00 m Size and no. of RWH tanks and Quantity 2 Nos. (165 cum) Location of the RWH tank(s): below Ground level Size, no of recharge pits and quantity: Nil Budgetary allocation (Capital cost and O&M Cost) Capital cost: Rs. 33.00Lakhs O&M Cost: Rs. 1.70Lakhs					

		Train n	- 1	· · · <u>· · · · · · · · · · · · · · · · </u>					
	27	UGT Tanks	Location(s) of the UGT Tank	c(s): Underground					
	Į		Domestic Tank = 372 cum						
	[Flushing =191 Cum Fire Tank= 100 cum						
	28	Storm water		en: South to Month					
	20	drainage	Natural Water drainage pattern: South to North Quantity of storm water:						
			Total Actual Discharge: 0.123	7 cum/sec					
			Total Design Discharge: 0.13						
			Size of SWD: B=0.40 m, D=						
		<u> </u>	, "						
	29	Sewage and	Sewage Generation (KLD):52	22					
-		waste water	STP Technology: MBBR						
			Capacity of STP (KLD): 550						
1			Location of the STP: Below g						
			DG Sets (during emergency):						
1			Budgetary allocation (Capital						
			Capital cost: Rs.113.00 Lakhs O&M Cost: Rs. 28.00 Lakhs						
Ì	30	Solid waste		onstruction and Construction Phase:					
-		management	Waste generation: Debris & ex	excavated material generated will be					
	i	<i>Q</i>	disposed as per the norms by	VVCMC.					
1				way debris: Debris to be disposed as					
	Ī		1	•					
1]		VVCMC debris management	plan.					
			Sr . Particulars	Management					
	ł								
1			1 Scrap metal	To be sold for recycling					
	i		2 Empty cement bags	To be sold to vendors.					
			3 Aggregates	To be used as a layer for internal					
l									
	ĺ		4 Wood	To be sold for reuse/recycling.					
			5 771-	To be used as china mosaic water					
l			5 Tiles						
			6 Empty Paint cans	for terraces and skirting purpose.					
l			_ 0 Empty Faint cans	To be sold to vendors.					
	}		Waste generation in the Operat	ion Phase					
ľ			Dry Waste (Kg/day): 840.00	ion i nase.					
			Wet Waste (Kg/day): 1241.00	ł					
			E waste (Kg/month): Not applie	cable					
	ł		Hazardous Waste (Kg/month):	Not applicable					
			Bio-medical Waste (kg/month)	(if applicable): Not applicable					
			STP Sludge (Dry Sludge): 33.0	0 kg/day					
			Mode of Disposal of Waste:						
				ugh recyclers					
			Dry waste: To be managed through recyclers. Wet Waste: To be processed in the Organic Waste Converter and						
			manure so obtained will be used	for landscaping.					
			E-Waste: NA						
			Hazardous Waste: NA						
		<u></u>	Biomedical Waste: NA						

		STP Sludge	(Dry Sludge): To be	used as manure,			
		Area requirement					
		Location(s) and total area provided for the storage and treatment					
		the solid waste:					
		Sr	. No. OWC deta		ulars		
		1		WC Model=60			
		2	OWC Cor	verter 14 sq.	m.		
		3	Curring ar	ea 20 sq.:	m		
		4	Raw Mate	rial 37 sq.:	m.		
		5	Area of Pl	ant 72 sq.:	m		
		Di	ıst Bibs (Green & Bl	ack)			
		1	Flats	33			
}		2	Shops	10			
		Capital cost	allocation (Capital co :: Rs. 10.00Lakhs Rs. 5.00Lakhs	st and O&M cost)			
31	Green Belt	Total RG ar					
İ	Development	RG area oth	er than green belt (Pl	ease specify for pla	ayground etc.)		
		n.c.	3 114.				
			der green belt: ground (Sq. m):				
!		_	G: 3271.235 Sq. m (1	5%)			
]		1 <u>*</u> ·	G: 3277.34 Sq. m (15	-			
		1 *	odium (Sq. m):170.0	••			
		Plantation					
			d list of trees species	to be planted in t	the ground RG:		
		nos. (existi	ng 317 + Proposed 53	3)			
		List of exist	ing trees :				
			OTANICAL NAME	NAME OF	QUANTIT		
		1 Co	cos nucifera	Coconut	10		
		2 Az	adirachta indica	Neem	12		
		3 Ar	eca catechu	Supari	2		
		4 Ph	oenix canariensis	Canari	4		
		5 Fig	cus religiosa	Pipal	5		
		6 Ps	idium guajava	Peru	3		
		7 Ar	nona squamosa	Sitafal	4		
		8 Al:	stonia scholaris	Sathpani	15		
		9 Sa	manea saman	Rain tree	1		
		10 De	lonix regia	Gulmohar	2		
		11 Dy	psis lutescens	Areka palm	15		
			stonia scholaris	Alistonia	20		
		13 Sa	raca asoca	Ashoka	8		

14	Exocarpos formis	Australian	1	
15	Terminalia catappa	Almond	4	ヿ
16	Syzygium cumini	Jamun	3	コ

SR	BOTANICAL NAME	NAME OF	QUANTIT
17	Araucaria columnaris	Chrismas tree	2
18	Peltophorum pterocarpum	Peltoparam	4
19	Ficus racemosa	Umber	1
20	Mangifera indica	Mango	6
21	Moringa oleifera	Shevga	12
22	Annona reticulata	Ram fal	2
23	Mimusops elengi	Bakul	25
24	Swietenia mahagoni	Mahugoni	20
25	Petunia	Petunia	20
26	Calendula sps	Marigold	8
27	Nyctanthes arbor-tristis	Parijat	4
28	Cinnamomum tamala	Tez patta	1
29	Citrus limetta	Sweet lime	1
33	Phyllanthus emblica	Amla	1
31	Mussaenda frondosa	Musanda	1
TOTA	AL		217

Sr. No.	Scientific Name	Common	Nos.
1	Michelia champaca	Champa	5
2	Syzygium cumini	Indian 111y	6
3	Polyalthia longifolia	Mast tree	8
4	Saraca asoca	Tree	8
5	Cassia fistula	Bahava	5
6	Nyctanthes arbor-tristis	Parijatak	5
7	Butea monosperma	Palas	2
8	Azadiracta indica	Neem	2
9	Samanea saman	Rain Tree	4
10	Delonix regia	Flame tree	4
<u> 11</u>	Prunus dulcis	Badam tree	4
	TOTAL	53	

Number and list of shrubs and bushes species to be planted in the podium RG: No

Number and list of trees species to be planted around the border of nallah/stream/pond (if any): Nil
Number, size, age and species of trees to be cut, trees to be

		transplanted: Nil NOC for the Tree cutting/transplantation/compensatory plantation, if any: Not Applicable						
32	Energy	Power supply: Maximum Demand: 4306 KW Connected Load: 6758 KW Source: MSEDCL Energy saving by non conventional method: Energy saving measures						
		Detail calculations &		22.00 %				
		S Items	Total elect. Demand conventiona cw)	Elect. Demand Using saving means (Units Saved (kw)	Energy		
		Energy Saving Parar	neters		<u> </u>			
		1 Road/ landscape- 60%	6.5	2.6	3.9	60%		
		2 Parking -T5	5.9	4.4	1.5	25%		
		3 LED lights- Lobby & staircase	69	9.1	60.3	87%		
		4 Lobby & e LED lights- 60% Solar	15.2	6.1	9.1	60%		
		5 Lift – rative Types	80.0	64.0	16	20%		
		6 Solar Hot water	4110	2261	1850	45%		
		Conventional Loads						
ļ		7 Plumbing system	92	92				
		8 OWC	7	7				
		9 STP	22	22				
		1 Fresh air ion Fan	3	3				
		1 Sub Station Ventilation	4	4				
		1 FF Plant Room Ventilation	4	4	·· -			
		1 Flats	4110	4110				
		1 Shops	170	170				

	П	Total		8699		6758	1940	
	-		aving for the		ct = 22			
	L							-: -
Į			e of ECBC		elines:	(Yes/no) (If yes,	then submit
a l	_	Section	· · · · · · · · · · · · · · · · · · ·		1	Complia	nce mot	hv
1	No		n Kequiren	acm		Сощрна	nce met	υ <u>γ</u>
	10	'''						
		Elec	trical Units s	saving	parame	eters (Calcı	ılation-b	ased)
	1	6.2.1	for minimu	m		hotwater ised solar s	•	ment met
	2	7.2.1.4	Exterior lig	hting	1) 60%	lighting i	ncluding	for Road.
	-		hin	-	pe &			, 101 11044,
			specified lin	1	-	shall be ke	pt on so	lar
]		system.		• • .	.,,
İ					2) Also	o other L	ights pi	ovided on
				s	saving l	uminaries l	like LEI	intsead of
				1	nalide la	amps.		
][ł				Time sw	ritch to be
				1	ational			
	_	721	 T			ring night n		
	3	7.3.1	Interior lig			_		ne lighting t by using
	ĺ		l to be with ir		clisity	snan oe o.	∠ w/sqi	t by using
			specified lin	1	ights in	stead of T8	3.	İ
	ſ] ⁻					ED would
[]	J			ю	wer de	nsity		İ
			1			han 1.3w/s	-	.
	ļ				0)60% (ut on	or Lobby &	x Staire	ase Lights
			1	P		/ Panels.		[]
	4		Lifts			egenerative	Type I	ift system
[]			ative	ile		J	- , p - *	
	- [system			20% energ		
-	_					d to conver		
[]	5		Ventilation I				on fans	provided
-	ĺ				o operat	te / within per	aniasihi.	
]}		j				munn per per per		
) sensors	. wiiiCilk,	operation
		Infr	astructure ba				measur	es
<u> </u>	5 8	2 1 2F	Fransformer	k	oltmete	ers/Ammete	ere for -	onitoria
]] :	~ °	L	ng	ne me		19/MIIIIIef	101 TO 101 T	iomioring
			o		_	nce & losse	es	
				Ĵ.	<u> </u>			

		6 8	3.2.2 Energ	y effici	of class category	ors used in pumps of services that would give fficiency (60%+)& less losses	
			3.2.3 Power on 3.2.4 Energ			Factor from 0.95 to 1 Meters for External Lighting, for	
,		9 8.	2.5.1 Cable ses	sizing	heating during w	al cables of derated capacity working thereby saving ent losses.	
<u> </u>		Capita O&M DG set Number	l cost: Rs.85 cost: Rs. 8.0 i:	5.00 Lak 00 Lakhs ity of th	hs s	d O&M cost) o be used: 1 X 250 KVA	
33	Environmental Management Plan	Constr Capita	uction Phase l cost	e (with I		and other details)	
	Budgetary allocation	Sr.	Method	Adopte	d	Cost (Rs. Lakhs/ year)	
		1	Water	Sprinkl	ling for	2.5	
		$\frac{1}{2}$			& safety	4.0	
		3.	Disinfe			1.5	
		4.	Health o		, -	3.0	
		Total				11.00	
	,	Operation Phase (with Break up): Capital cost O&M cost (Please ensure manpower and other details)					
		Sr. No	Metho Adopted	d	Setting-Up Cost (Rs. akhs)		
i		1	Rain Water Harvesting		33.00	1.70	

						
		2	MSW	10.00	5.00	
		3	STP	113.00	28.00	
		4	Energy Conservation	85.0	8.0	
		5	Landscaping	18.00	4.0	
		Tota	ıl	259.00	46.7	
		Quantum and generation of Corpus Fund and Commitment Responsibility for further O & M After occupancy, Co-Op societies will be formed. The societies m a federation. The Operation and Maintenance of Environmental management s (EMF) shall be taken care by the developers for first three years. Afterwards, EMF shall be handed over to society/ federation. Funds for recurring cost on EMP shall be generated from the				
		of the society by specifically				
34	Traffic	mentioning in the sale agreement Nos. of the junction to the main road & design of confluence				
34	Management	Nos. of the junction to the main road & design of confidence				
	Managoment	Parking details:				
1		Number and area of basement: 1 No. (1826.22 sq.m.)				
		Number and area of podia: 1 no. (1719.33sq.m.)				
		Stilt parking area: 517.29 sq. m				
		Open Parking Area: 733.40sq.m.				
		Total Parking Area: 1250.69 sq.m.				
1		Area Per Car:				
		Basement = 23.12 sq.m. (Stack Parking)				
1		Podium = 19.10 sq.m. (Stack Parking)				
	}	2-Wheeler: 854 Nos.				
Ì		4-Wheeler: 178 Nos.				
]		Public	Public Transport: Nil			
		N7' 147.				
Width of all internal roads: 6.00 to 35 CRZ/RRZ NA				: 6.00 to 9.00	m wide internal road	
33	clearance	NA				
	obtained, if any					
36	Distance from	Tungar	eshwar Forest Area	= 8.20 km/se	rial distance)	
	Protected	Tungareshwar Forest Area = 8.20 km(aerial distance)				
}	Area/Critically]			}	
	Polluted					
	areas/Eco-	1				
	sensitive areas					
	/inter-State	1				
	boundaries					

^{3.} The proposal has been considered by SEIAA in its 91st & 102nd meetings & decided to accord environmental clearance to the said project under the provisions of Environment Impact Assessment Notification, 2006 subject to implementation of the following terms and conditions:

General Conditions for Pre-construction phase:-

- (i) This environment clearance is issued subject to restricting total built up area of 21,292.51 Sq.m as approved by Local Planning Authority.
- This environmental clearance is issued subject to land use verification. Local (ii) authority / planning authority should ensure this with respect to Rules, Regulations, Government Resolutions. Circulars. etc. issued if Notifications. Judgments/orders issued by Hon'ble High Court, Hon'ble NGT, Hon'ble Supreme Court regarding DCR provisions, environmental issues applicable in this matter should be verified. PP should submit exactly the same plans appraised by concern SEAC and SEIAA. If any discrepancy found in the plans submitted or details provided in the above para may be reported to environment department. This environmental clearance issued with respect to the environmental consideration and it does not mean that State Level Impact Assessment Authority (SEIAA) approved the proposed land use.
- (iii) PP to ensure that the fire staircases open outside the building No. 5, wing A and D.
- (iv) PP to ensure that no fire staircase or lift goes to the basement and shall terminate on ground level only.
- (v) PP to provide minimum 3 meter height to the basement and provide adequate ventilation on ground level ensuring that no water ingress takes place in the basement through ramp in monsoon season by providing appropriate coverings.
- (vi) E-waste shall be disposed through Authorized vendor as per E-waste (Management and Handling) Rules, 2016.
- (vii) This environmental clearance is issued subject to obtaining NOC from Forestry & Wild life angle including clearance from the standing committee of the National Board for Wild life as if applicable & this environment clearance does not necessarily implies that Forestry & Wild life clearance granted to the project which will be considered separately on merit.
- (viii) PP has to abide by the conditions stipulated by SEAC & SEIAA.
- (ix) The height, Construction built up area of proposed construction shall be in accordance with the existing FSI/FAR norms of the urban local body & it should ensure the same along with survey number before approving layout plan & before according commencement certificate to proposed work. Plan approving authority should also ensure the zoning permissibility for the proposed project as per the approved development plan of the area.
- (x) "Consent for Establishment" shall be obtained from Maharashtra Pollution Control Board under Air and Water Act and a copy shall be submitted to the Environment department before start of any construction work at the site.
- (xi) All required sanitary and hygienic measures should be in place before starting construction activities and to be maintained throughout the construction phase.

General Conditions for Construction Phase-

- (i) Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche and First Aid Room etc.
- (ii) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal

of wastewater and solid wastes generated during the construction phase should be ensured.

- (iii) The solid waste generated should be properly collected and segregated, dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- (iv) Disposal of muck during construction phase should not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (v) Arrangement shall be made that waste water and storm water do not get mixed.
- (vi) All the topsoil excavated during construction activities should be stored for use in horticulture / landscape development within the project site.
- (vii) Additional soil for leveling of the proposed site shall be generated within the sites (to the extent possible) so that natural drainage system of the area is protected and improved.

1

- (viii) Green Belt Development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with the local DFO/Agriculture Dept.
- (ix) Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- (x) Construction spoils, including bituminous material and other hazardous materials must not be allowed to contaminate watercourses and the dumpsites for such material must be secured so that they should not leach into the ground water.
- (xi) Any hazardous waste generated during construction phase should be disposed off as per applicable rules and norms with necessary approvals of the Maharashtra Pollution Control Board.
- (xii) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environments (Protection) Rules prescribed for air and noise emission standards.
- (xiii) The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from concern authority shall be taken.
- (xiv) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- (xv) Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to

- reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/MPCB.
- (xvi) Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100Km of Thermal Power Stations).
- (xvii) Ready mixed concrete must be used in building construction.
- (xviii) The approval of competent authority shall be obtained for structural safety of the buildings due to any possible earthquake, adequacy of firefighting equipment's etc. as per National Building Code including measures from lighting.
- (xix) Storm water control and its re-use as per CGWB and BIS standards for various applications.
- (xx) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.

3

- (xxi) The ground water level and its quality should be monitored regularly in consultation with Ground Water Authority.
- (xxii) The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the MPCB and Environment department before the project is commissioned for operation. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treated effluent emanating from STP shall be recycled/refused to the maximum extent possible. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by decentralized treatment should be done. Necessary measures should be made to mitigate the odour problem from STP.
- (xxiii) Permission to draw ground water and construction of basement if any shall be obtained from the competent Authority prior to construction/operation of the project.
- (xxiv) Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.
- (xxv) Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- (xxvi) Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.
- (xxvii) Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- (xxviii)Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be

in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non-conventional energy source as source of energy.

- (xxix) Diesel power generating sets proposed as source of backup power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.
- (xxx) Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.
- (xxxi) Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- (xxxii) Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspiration for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- (xxxiii) The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- (xxxiv)Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.
- (xxxv) Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.
- (xxxvi)Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this department and MPCB.

General Conditions for Post- construction/operation phase-

(i) Project proponent shall ensure completion of STP, MSW disposal facility, green belt development prior to occupation of the buildings. As agreed during the SEIAA meeting, PP to explore possibility of utilizing excess treated water in the adjacent area for gardening before discharging it into sewer line. No physical occupation or allotment will be given unless all above said environmental infrastructure is installed and made functional including water requirement in Para 2. Prior certification from appropriate authority shall be obtained.

- (ii) Wet garbage should be treated by Organic Waste Converter and treated waste (manure) should be utilized in the existing premises for gardening. And, no wet garbage will be disposed outside the premises. Local authority should ensure this.
- (iii) Local body should ensure that no occupation certification is issued prior to operation of STP/MSW site etc. with due permission of MPCB.
- (iv) A complete set of all the documents submitted to Department should be forwarded to the Local authority and MPCB.
- (v) In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Department.
- (vi) A separate environment management cell with qualified staff shall be set up for implementation of the stipulated environmental safeguards.
- (vii) Separate funds shall be allocated for implementation of environmental protection measures/EMP along with item-wise breaks-up. These cost shall be included as part of the project cost. The funds earmarked for the environment protection measures shall not be diverted for other purposes and year-wise expenditure should reported to the MPCB & this department.
- (viii) The project management shall advertise at least in two local newspapers widely circulated in the region around the project, one of which shall be in the Marathi language of the local concerned within seven days of issue of this letter, informing that the project has been accorded environmental clearance and copies of clearance letter are available with the Maharashtra Pollution Control Board and may also be seen at Website at http://ec.maharashtra.gov.in.
- (ix) Project management should submit half yearly compliance reports in respect of the stipulated prior environment clearance terms and conditions in hard & soft copies to the MPCB & this department, on 1st June & 1st December of each calendar year.
- (x) A copy of the clearance letter shall be sent by proponent to the concerned Municipal Corporation and the local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the Company by the proponent.
- (xi) The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM. SO₂, NOx (ambient levels as well as stack emissions) or critical sector parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
- (xii) The project proponent shall also submit six monthly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB.

- 1= 1
- (xiii) The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF by e-mail.
- 4. The environmental clearance is being issued without prejudice to the action initiated under EP Act or any court case pending in the court of law and it does not mean that project proponent has not violated any environmental laws in the past and whatever decision under EP Act or of the Hon'ble court will be binding on the project proponent. Hence this clearance does not give immunity to the project proponent in the case filed against him, if any or action initiated under EP Act.
- 5. In case of submission of false document and non-compliance of stipulated conditions, Authority/ Environment Department will revoke or suspend the Environmental Clearance without any intimation and initiate appropriate legal action under Environmental Protection Act, 1986.
- 6. The Environment department reserves the right to add any stringent condition or to revoke the clearance if conditions stipulated are not implemented to the satisfaction of the department or for that matter, for any other administrative reason.
- 7. Validity of Environment Clearance: The environmental clearance accorded shall be valid for a period of 7 years as per MoEF&CC Notification dated 29th April, 2015.
- 8. In case of any deviation or alteration in the project proposed from those submitted to this department for clearance, a fresh reference should be made to the department to assess the adequacy of the condition(s) imposed and to incorporate additional environmental protection measures required, if any.
- 9. The above stipulations would be enforced among others under the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986 and rules there under, Hazardous Wastes (Management and Handling) Rules, 1989 and its amendments, the public Liability Insurance Act, 1991 and its amendments.

10. Any appeal against this environmental clearance shall lie with the National Green Tribunal (Western Zone Bench, Pune), New Administrative Building, 1st Floor, D-, Wing, Opposite Council Hall, Pune, if preferred, within 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

Member Secretary, SEIAA

Copy to:

- Shri. Johny Joseph, Chairman, IAS (Retd.). SEAC-II, office of the Lokayukta and New Up- Lokayukta, New Administrative Building, 1st floor, Madam Cama Road, Mumbai.
- 2. Additional Secretary, MOEF, 'MoEF & CC, Indira Paryavaran Bhavan, Jorbagh Road, Aliganj, New Delhi-110003.

- 3. The CCF, Regional Office, Ministry of Environment and Forest (Regional Office, Western Region, Kendriya Paryavaran Bhavan, Link Road No- 3, E-5, Ravi-Shankar Nagar, Bhopal- 462 016). (MP).
- 4. IA- Division, Monitoring Cell, MoEF & CC, Indira Paryavaran Bhavan, Jorbagh Road, Aliganj, New Delhi-110003.
- 5. Managing Director, MSEDCL, MG Road, Fort, Mumbai
- 6. Collector, Thane.
- 7. Commissioner, Vasai Virar City Municipal Council (VVCMC)
- 8. Member Secretary, Maharashtra Pollution Control Board, with request to display a copy of the clearance.
- 9. Regional Office, MPCB, Thane
- 10. Select file (TC-3)

 (EC uploaded on)